

DATA SHEET

Product Type
Item Number

Filter Cartridge
NF40515

Dimensions:	Height	39"
	Outside Diameter	16.00"
	Inside Diameter	11.50"
Top End Cap:	Material	Galvanneal (14 ga)
	Style	Open with 17.75" x 21" Flange
Bottom End Cap:	Material	Electrogalvanized or Galvanneal (18 ga)
	Style	Closed
	Bolt Hole	None
Gasket:	5/16" thick x 1/2" wide EPDM/Neoprene sponge gasket applied around perimeter of flange	
Inner Retainer:	Galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	Four (4) Woven Bands	
Nominal Filter Media Area:	350 ft ²	
Media Type:	Cellulose Blend with ProTura Nanofiber Technology – Flame Retardant	
Permeability:	20 cfm/ft ² @ 0.5" w.g.	
Maximum Temperature:	200° F (93° C)	
Minimum Efficiency Reporting Value:	MERV 15	
Fractional Efficiency:	See Chart Below	

Particle size ranges - µm			
Minimum average efficiency before dust loading	(E1) 0.3 – 1.0	(E2) 1.0 – 3.0	(E3) 3.0 – 10.0
	89.0%	98.3%	99.8%

All above data is nominal and provided for information only and is subject to change. All metric conversions are approximate.

